


Allan Deviation $\sigma_y(\tau)$



Input 5.0 MHz 13 dBm

Allan Deviation $\sigma_y(\tau)$

$\tau_0 = 100 \text{ ms}$	Avg. Time (s)	Allan Deviation $\sigma_y(\tau)$	NEQ BW = 5
	0.1	4.696×10^{-11}	
	0.2	2.610×10^{-11}	
	0.4	1.304×10^{-11}	
	1	5.30×10^{-12}	
	2	3.80×10^{-12}	
	4	2.38×10^{-12}	
	10	1.87×10^{-12}	
	20	1.45×10^{-12}	
	40	1.52×10^{-12}	
	100	1.66×10^{-12}	
	200	2.03×10^{-12}	
	400	2.9×10^{-12}	
	1000	5.7×10^{-12}	
	2000	1.2×10^{-11}	


24/03/2007 15:13:48
2h 0m

TSC 5120A

Phase Difference

4.0x10⁻⁰⁹ s/div

Center: -1.4944x10⁻⁰⁷ s



60s/div


Input 5.0 MHz 13 dBm

Reference 5.0 MHz 13 dBm

Frequency Difference

2.0x10⁻¹¹ /div

Center: -8.787x10⁻¹¹



60s/div

Input 5.0 MHz 13 dBm

Reference 5.0 MHz 13 dBm


Frequency Counter

Sample Time (s)	Frequency (MHz)
1	5.0000001132749
10	5.00000011328071
100	5.000000113296832
1000	5.000000113264186

Reference Frequency: 5.0 MHz (auto)

$\mathcal{L}(f)$ Phase Noise at 5.0 MHz (dBc/Hz)

20 dB/Div



Input 5.0 MHz 13 dBm

Reference 5.0 MHz 13 dBm