


# Allan Deviation $\sigma_y(\tau)$

NEQ BW = 0.5 Hz

$\tau_0 = 1$  s



Averaging Time  $\tau$ , seconds

Input 10.0 MHz 7 dBm

Reference 5.0 MHz 12 dBm

# Allan Deviation $\sigma_y(\tau)$


Avg. Time (s)	Allan Deviation $\sigma_y(\tau)$	Noise Floor
1	$7.41 \times 10^{-12}$	$1.20453 \times 10^{-13}$
2	$5.87 \times 10^{-12}$	$8.84457 \times 10^{-14}$
4	$4.55 \times 10^{-12}$	$6.03898 \times 10^{-14}$
10	$3.65 \times 10^{-12}$	$3.84546 \times 10^{-14}$
20	$4.1 \times 10^{-12}$	$2.76320 \times 10^{-14}$
40	$5.9 \times 10^{-12}$	$2.18379 \times 10^{-14}$
100	$7.0 \times 10^{-12}$	
200	$1.2 \times 10^{-11}$	
400	$2.1 \times 10^{-11}$	

$\tau_0 = 1 \text{ s}$       NEQ BW = 0.5 Hz

# Phase Difference

5.0x10<sup>-09</sup> s/div

Center: 2.552x10<sup>-08</sup> s



60s/div


Input 10.0 MHz 7 dBm

Reference 5.0 MHz 12 dBm

# Frequency Difference

2.0x10<sup>-11</sup> /div

Center: 5.791x10<sup>-11</sup>



60s/div

Input 10.0 MHz 7 dBm

Reference 5.0 MHz 12 dBm

# Frequency Counter


Sample Time (s)	Frequency (MHz)
1	9.9999998444989
10	9.99999984432071
100	9.999999844338947

Reference Frequency: 5.0 MHz (auto)

# $\mathcal{L}(f)$ Phase Noise at 10.0 MHz (dBc/Hz)

Mx: 1.000977 Hz  $\Delta$ Mx: 10009.77 Hz  $\Delta$ x: -10008.8  
 My: -79.3 dBc/Hz  $\Delta$ My: -153.7 dBc/Hz  $\Delta$ y: 74.5

10 dB/Div



Offset Frequency (Hz)

Time Constant:  $\infty$

Input 10.0 MHz 7 dBm

Reference 5.0 MHz 12 dBm